



EPOXY FLOOR PAINT

(Solvent free)

It is a solvent-free, epoxy-based, two-component paint with excellent adhesion to all surfaces.

APPLICATION AREAS

-Can be applied to all types of surfaces such as wood, parquet, laminate, ceramic, porcelain, tile, marble, metal, stone, walls, etc.




APPLICATION INFORMATION

Surface preparation: First, the surface to be applied is cleaned of dust, dirt and oil. If there are areas that need repair, they are repaired in advance and the surface is sanded. **Application method:** Demarin Epoxy Coating is ready to use, do not dilute. The product is mixed homogeneously with its hardener in a 4/1 ratio (4 epoxy / 1 hardener) in a box for 5 minutes with the help of a mixer. This product can be applied to the surface with a roller or squeegee. Epoxy mixed with hardener should be used within 40 minutes. The time to reach mechanical resistance is 24 hours. The air temperature where the product will be applied is +5 - 30°C. If you have applied white and its shades, Demarin Ultragloss Liquid Glass must be applied after 1 week and 7 days, otherwise there may be changes in color.

TECHNICAL SPECIFICATIONS

- **Density:** 1.12 ± 0.02 Mixture
- **Color:** All special colors can be made
- **Brightness:** Shiny, matte as preferred
- **Thinner:** Not thinned
- **Consumption:** 3-4 m²/kg (1-2 m²/kg if thick casting)
- **Solvent:** -



Attention


The applied surface must be protected from water, moisture and mechanical impacts for at least 24 hours during and after application.




PACKAGING & STORAGE

- **Packaging:** 1, 4 and 20 kg metal cans
- **Storage Temperature:** +5 - 30 °C
- **Shelf Life:** If stored in original, unopened and undamaged packaging, the primer is suitable for 24 months and the hardener is suitable for 12 months from the date of production.
- **Storage Conditions:** Store in a dry and cool environment with the packaging lids tightly closed.





Customizable with color chart



Pedestrian traffic

Material	Concrete	Marble	Wood	Tile	Metal
Dry to the Touch	5 hours	5 hours	5 hours	5 hours	5 hours
Recommended Application	Roller, squeegee	Roller, squeegee	Roller, squeegee	Roller, squeegee	Roller, squeegee
Complete Drying	24 hours	24 hours	24 hours	24 hours	24 hours