

DEMACOAT P.U. POOL PAINT



It is a two-component, polyurethane-based, flexible, bright and decorative pool paint that is resistant to pool chemicals, has high mechanical and physical resistance, and is UV resistant. It also provides waterproofing.

USAGE AREAS

-It can be used safely in old pools and water tanks (except drinking water).



APPLICATION INFORMATION

Surface preparation: First, the surface to be applied is cleaned of dust, dirt and oil. If there are areas that need repair, they are repaired in advance and the surface is sanded very well. If sanding is not done, the paint may not adhere to the surface. **Application method:** Demacoeat Pool Paint is ready to use, if you wish, you can dilute it with 10% Demarin polyurethane thinner. The product is mixed homogeneously with its hardener in a 3/1 ratio (3 paint / 1 hardener) in a box for 4 minutes with the help of a mixer. This product can be applied to the surface with a roller, brush or paint gun. The paint mixed with the hardener should be used within 40 minutes. The time to reach mechanical resistance is 24 hours. The air temperature where the product will be applied is +5 - 30°C.

TECHNICAL SPECIFICATIONS

- **Density:** 1.40 ± 0.02 Mixture
- **Color:** Blue, all special colors can be made
- **Gloss:** Shiny, matte as preferred
- **Thinner:** 10% Demarin Polyurethane thinner
- **Consumption:** 8-10 m²/kg
- **Solvent:** Thinner
- **Gun Nozzle Diameter:** 1.2 – 1.4 mm


PACKAGING & STORAGE

- **Packaging:** 1, 4 and 20 kg metal cans
- **Storage Temperature:** +5 - 30 °C
- **Shelf Life:** If stored in original, unopened and undamaged packaging, the primer is suitable for 24 months and the hardener is suitable for 12 months from the date of production.
- **Storage Conditions:** Store in a dry and cool environment with the packaging lids tightly closed.



Attention

The applied surface must be protected from water, moisture and mechanical impacts for at least 24 hours during and after application.



Customizable
with color chart



Pedestrian traffic



Ultraviolet
resistance

Material



Concrete



Marble



Wood



Tile



Metal

Waiting Time Between Floors

2 hours

2 hours

2 hours

2 hours

2 hours

Dry to the Touch

4 hours

4 hours

4 hours

4 hours

4 hours

Recommended Application

Roller, Brush

Roller, Brush

Roller, Brush,
Airless

Roller, Brush,
Airless

Roller, Airless

Complete Drying

48 hours

48 hours

48 hours

48 hours

48 hours