



990 P.U. PRIMER

It is a polyurethane-based, single-component solvent-containing impregnating primer with strong penetration that is applied to wood and concrete surfaces.

AREAS OF USE

-It is used in the impregnation of wooden surfaces in boat and yacht production and maintenance, in the priming of surfaces such as concrete, eternit mosaic and to prevent dust. It is used in putty applications of all kinds of wooden boats and as a primer and protective impregnation under varnish.

APPLICATION INFORMATION

Surface preparation: First, the surface to be applied is cleaned of dust, dirt and oil. If there are areas that need repair, they are repaired in advance and the surface is sanded. **Application method:** 990 Impregnated Primer is ready to use, but if you wish, you can dilute it by 5% with Demarin polyurethane thinner. The product is mixed homogeneously in the box for 1 minute with a mixer. This product can be applied to the surface with a roller, brush or paint gun. At least 8 hours should be waited between coats. The time to reach mechanical resistance is 24 hours. The air temperature where the product will be applied is +5 - 30°C.

TECHNICAL SPECIFICATIONS

- **Density:** 1.60 ± 0.02 g/cm³ Mixture
- **Color:** Transparent
- **Brightness:** Shiny
- **Thinner:** Can be diluted by 5%
- **Consumption:** 5-6 m²/kg
- **Solvent:** Thinner
- **Gun Nozzle Diameter:** 1.2 – 1.4 mm

PACKAGING & STORAGE

- **Packaging:** 1, 4 and 15 kg metal cans
- **Storage Temperature:** +5 - 30 °C
- **Shelf Life:** Suitable for use for 24 months from the date of production if stored in original, unopened and undamaged packaging.
- **Storage Conditions:** Store in a dry and cool environment with the packaging lids tightly closed.



Attention

The applied surface must be protected from water, moisture and mechanical impacts for at least 24 hours during and after application.



Customizable
with color chart



Pedestrian traffic



Ultraviolet
resistance

Material



Concrete



Marble



Wood



Tile



Metal

Waiting Time Between Floors	2 hours	2 hours	2 hours	2 hours	2 hours
Dry to the Touch	4 hours	4 hours	4 hours	4 hours	4 hours
Recommended Application	Roller, Brush	Roller, Brush	Roller, Brush	Roller, Brush	Roller, Airless
Complete Drying	24 hours	24 hours	24 hours	24 hours	24 hours