



SÜLYEN PRIMER

It is an alkyd resin based, surface tolerant paint containing anticorrosive pigment.

AREAS OF USE

-Used as a primer on iron, steel and wooden surfaces before air-drying synthetic topcoat paints.

APPLICATION INFORMATION

Surface preparation: First, the surface to be applied is cleaned of dust, dirt and oil. If there are areas that need repair, they are repaired in advance and the surface is sanded. **Application method:** Sülyen Primer is ready to use, do not dilute. The product is mixed homogeneously in the box for 1 minute with the help of a mixer. This product can be applied to the surface with a roller, brush or paint gun. At least 2 hours should be waited between coats. The time to reach mechanical resistance is 24 hours. The air temperature where the product will be applied is +5 - 30°C.

TECHNICAL SPECIFICATIONS

- **Density:** 1.40 ± 0.10 Mixture
- **Color:** White
- **Brightness:** Matt
- **Thinner:** Not Thinned
- **Consumption:** 8-10 m²/kg
- **Solvent:** Thinner
- **Gun Nozzle Diameter:** 1.2 – 1.4 mm

PACKAGING & STORAGE

- **Packaging:** 1, 3 and 20 kg metal cans
- **Storage Temperature:** +5 - 30 °C
- **Shelf Life:** Suitable for use for 24 months from the date of production if stored in original, unopened and undamaged packaging.
- **Storage Conditions:** Store in a dry and cool environment with the packaging lids tightly closed.



Attention

The applied surface must be protected from water, moisture and mechanical impacts for at least 24 hours during and after application.



Customizable
with color chart



Pedestrian traffic

Material	 Concrete	 Marble	 Wood	 Tile	 Metal
Waiting Time Between Floors	2 hours	2 hours	2 hours	2 hours	2 hours
Dry to the Touch	4 hours	4 hours	4 hours	4 hours	4 hours
Recommended Application	Roller, Brush	Roller, Brush	Roller, Brush	Roller, Brush	Roller, Airless
Complete Drying	24 hours	24 hours	24 hours	24 hours	24 hours