



EXTRA COPPER ADDITIVE

Increases the strength of antifouling paint. Provides longer lasting protection than normal.

AREAS OF USE

-Used with LL and SPC antifouling paint systems.

APPLICATION INFORMATION

Application method: It is a powder chemical additive that can be added to LL and SPC antifouling paint systems.


TECHNICAL SPECIFICATIONS

Colors: Red, Blue

PACKAGING & STORAGE

- **Packaging:** 0.5 and 1 kg metal cans
- **Storage Temperature:** +5 - 30 °C
- **Shelf Life:** Suitable for use for 5 years from the date of production if stored in original, unopened and undamaged packaging.
- **Storage Conditions:** Store in a dry and cool environment with the packaging lids tightly closed.

RENKLER



DEMASILVER PRIMER

It is a vinyl based single component metallic antifouling paint primer. It is used before the application of antifouling paints and to isolate old antifouling painted surfaces.

USAGE AREAS

-Used in the underwater lines of wooden, steel, fiberglass boats.

APPLICATION INFORMATION

Surface preparation: First, the surface to be applied is cleaned of dust, dirt and oil. If there are areas that need repair, they are repaired with Demarin Epofiller epoxy putty and the surface is sanded. **Application method:** Demasilver Antifouling Paint Primer is ready to use, but if you wish, you can dilute it by 10% with Demarin antifouling paint thinner. The product is mixed homogeneously in the box for 2 minutes with a mixer. This product can be applied to the surface with a roller, brush or paint gun. The air temperature where the product will be applied is +5 - 30°C.

TECHNICAL SPECIFICATIONS

- **Density:** 1.40 ± 0.10 g/cm³ Mixture
- **Color:** Metallic gray
- **Gloss:** Matt
- **Thinner:** Can be diluted by 10%
- **Consumption:** 5-6 m²/kg
- **Solvent:** Thinner
- **Gun Nozzle Diameter:** 1.2 – 1.4 mm



Attention

The applied surface must be protected from water, moisture and mechanical impacts for at least 24 hours during and after application.

PACKAGING & STORAGE

- **Packaging:** 1, 3 and 18 kg metal cans
- **Storage Temperature:** 5 - 30 °C
- **Shelf Life:** Suitable for use for 2 years from the date of production if stored in original, unopened and undamaged packaging.
- **Storage Conditions:** Store in a dry and cool environment with the packaging lids tightly closed.