



SPEEDLINE ANTIFOULING

It is a highly friction resistant antifouling paint used in speedboats. It is specially designed to protect marine surfaces against bacteria, algae, marine life and microorganisms. It is used in medium speed and fast moving boats. It is suitable for over 30 knots.

USAGE AREAS

-Used in the underwater lines of wooden, steel, fiberglass boats.

APPLICATION INFORMATION

Surface preparation: First, the surface to be applied is cleaned of dust, dirt and oil. If there are areas that need repair, they are repaired with Demarin Epofiller epoxy putty and the surface is sanded. If Demasilver antifouling primer has not been applied to the surface before application, the surface is primed, waited for 8 hours and antifouling paint is applied. If Demarin Speedline Antifouling has been applied before, you do not need to prime. **Application method:** Speedline Antifouling is ready to use, but if you wish, you can dilute it by 10% with Demarin antifouling paint thinner. The product is mixed homogeneously in the box for 2 minutes with a mixer. This product can be applied to the surface with a roller, brush or paint gun. We recommend 2 coats. At least 6 hours should be waited between coats. The air temperature where the product will be applied is +5 - 30°C.

TECHNICAL SPECIFICATIONS

- **Density:** 1.65 ± 00.2 g/cm³ Mixture
- **Colors:** White, Red, Blue, Black, Green
- **Gloss:** Matt
- **Thinner:** 10% thinnable
- **Consumption:** 5-6 m²/kg
- **Solvent:** Thinner
- **Gun Nozzle Diameter:** 1.2 – 1.4 mm

PACKAGING & STORAGE


- **Packaging:** 1, 3, 8 and 20 kg metal cans
- **Storage Temperature:** +5 - 30 °C
- **Shelf Life:** Suitable for use for 24 months from the date of production if stored in original, unopened and undamaged packaging.
- **Storage Conditions:** Store in a dry and cool environment with the packaging lids tightly closed.



Attention

The applied surface must be protected from water, moisture and mechanical impacts for at least 24 hours during and after application.

RENKLER



White



Green



Red



Black



Marine Blue



below waterline

Primer
Demasilver
Antifouling primer

Antifouling
Speedline Antifouling