



# GALVANIZED PAINT

Epoxy resin reaction drying metallic top coat paint. It is an anticorrosive paint with high adhesion strength to the surface. It is also used as a decorative paint on all kinds of metal surfaces.



## AREAS OF USE


-It is a product applied on galvanized and similar aluminum zinc and nonmetals.

## APPLICATION INFORMATION

**Surface preparation:** First, the surface to be applied is cleaned of dust, dirt and oil. If there are areas that need repair, they are repaired in advance and the surface is sanded. **Application method:** Galvanized Paint is ready to use, if you wish, you can dilute it by 10% with Demarin epoxy thinner. The product is mixed homogeneously in the box for 2 minutes with a mixer. This product can be applied to the surface with a roller, brush or paint gun. The time to reach mechanical resistance is 24 hours. The air temperature where the product will be applied is +5 - 30°C.

## TECHNICAL SPECIFICATIONS

- **Density:** 1.50 ± 0.02 Mixture
- **Color:** Metallic gray
- **Gloss:** Semi-gloss
- **Thinner:** 10% Demarin Epoxy thinner
- **Consumption:** 8-10 m<sup>2</sup>/kg
- **Solvent:** Thinner
- **Gun Nozzle Diameter:** 1.2 – 1.4 mm



**Attention**

The applied surface must be protected from water, moisture and mechanical impacts for at least 24 hours during and after application.








## PACKAGING & STORAGE

- **Packaging:** 1, 3 and 18 kg metal cans
- **Storage Temperature:** +5 - 30 °C
- **Shelf Life:** If stored in original, unopened and undamaged packaging, the primer is suitable for 24 months and the hardener is suitable for 12 months from the date of production.
- **Storage Conditions:** Store in a dry and cool environment with the packaging lids tightly closed.





Customizable with color chart

Material					
	Concrete	Marble	Wood	Tile	Metal
Dry to the Touch	x	x	x	x	2 hours
Recommended Application	x	x	x	x	Roller, Airless
Complete Drying	x	x	x	x	24 hours