



NON-SLIP SANDY PAINT

It is a ready-to-use, air-drying, friction-resistant paint that can be applied in high film thicknesses, has non-slip properties in dry, wet and oily conditions, is solvent-based, transparent and white, has high alkali resistance and is UV-resistant with special additives.

USAGE AREAS

-It can be used safely on all slippery surfaces. It is very suitable for gyms, tennis courts, basketball courts, schools, parking lots, poolsides and stairs.



APPLICATION INFORMATION

Surface preparation: First, the surface to be applied is cleaned of dust, dirt and oil. If there are areas that need repair, they are repaired in advance and the surface is sanded. **Application method:** Non-Slip Paint is ready to use, do not dilute. The product is mixed homogeneously in the box for 1 minute with the help of a mixer. This product can be applied to the surface with a roller, brush or paint gun. The time to reach mechanical resistance is 24 hours. The air temperature where the product will be applied is +5 - 30°C.

TECHNICAL SPECIFICATIONS

- **Density:** 1.50 ± 0.02 Mixture
- **Color:** White, Transparent
- **Gloss:** Semi-gloss
- **Thinner:** Not thinned
- **Consumption:** 8-10 m²/kg
- **Solvent:** Thinner



Attention

The applied surface must be protected from water, moisture and mechanical impacts for at least 24 hours during and after application.



PACKAGING & STORAGE

- **Packaging:** 1, 3 and 15 kg metal cans
- **Storage Temperature:** +5 - 30 °C
- **Shelf Life:** If stored in original, unopened and undamaged packaging, the primer is suitable for 24 months and the hardener is suitable for 12 months from the date of production.
- **Storage Conditions:** Store in a dry and cool environment with the packaging lids tightly closed.



Customizable
with color chart



Pedestrian traffic

Material



Concrete



Marble



Wood



Tile



Metal

Dry to the Touch

2 hours

2 hours

2 hours

2 hours

2 hours

Recommended Application

Roller, Brush

Roller, Brush

Roller, Brush

Roller, Brush

Roller

Complete Drying

24 hours

24 hours

24 hours

24 hours

24 hours