



BILGE PAINT

It is a modified thermoplastic air-drying resin based solvent bilge paint. It is applied to the lowest part where water leaking from the ship and oils flowing from the engine and boiler rooms are stored. It prevents bilge water from penetrating the wood thanks to its molecular structure. It forms a semi-matte film on the surface it is applied. It can be applied directly on old paints.

USAGE AREAS

-Used to paint the bilge section of boats.

APPLICATION INFORMATION


Surface preparation: First, the surface to be applied is cleaned of dust, dirt and oil. If there are areas that need repair, they are repaired in advance and the surface is sanded. **Application method:** Bilge Paint is ready to use, do not dilute. The product is mixed homogeneously in the box for 2 minutes with a mixer. This product can be applied to the bilge with a roller, brush or paint gun. The time to reach mechanical resistance is 24 hours. The air temperature where the product will be applied is +5 - 30°C.

TECHNICAL SPECIFICATIONS

- **Density:** 1.50 ± 0.02 Mixture
- **Color:** White
- **Gloss:** Semi-matte
- **Thinner:** Not thinned
- **Consumption:** 8-10 m²/kg
- **Solvent:** Thinner
- **Gun Nozzle Diameter:** 1.2 – 1.4 mm

PACKAGING & STORAGE

- **Packaging:** 1, 3 and 18 kg metal cans
- **Storage Temperature:** +5 - 30 °C
- **Shelf Life:** If stored in original, unopened and undamaged packaging, the primer is suitable for 24 months and the hardener is suitable for 12 months from the date of production.
- **Storage Conditions:** Store in a dry and cool environment with the packaging lids tightly closed.

**Attention**

The applied surface must be protected from water, moisture and mechanical impacts for at least 24 hours during and after application.





Customizable
with color chart

Material					
Dry to the Touch	3 hours	3 hours	3 hours	3 hours	3 hours
Recommended Application	Roller, Brush	Roller, Brush	Roller, Brush	Roller, Brush	Roller, Airless
Complete Drying	24 hours	24 hours	24 hours	24 hours	24 hours