



EPOXY TOP COAT PAINT

It is a two-component, reaction-drying epoxy resin-based, top coat gloss paint that protects metals working under heavy conditions against rust and corrosion.

AREAS OF USE

-Can be used on all surfaces such as wood, metal, concrete, composite, fiber and polyester etc.

APPLICATION INFORMATION


Surface preparation: First, the surface to be applied is cleaned of dust, dirt and oil. If there are areas that need repair, they are repaired in advance and the surface is sanded. **Application method:** Epoxy Topcoat Paint is ready to use. You can dilute it with 10% Demarin epoxy thinner. The product is mixed homogeneously with its hardener in a 4/1 ratio (4 paint / 1 hardener) in a box for 5 minutes with the help of a mixer. This product can be applied to the surface with a roller, brush or paint gun. The paint mixed with the hardener should be used within 40 minutes. The time to reach mechanical resistance is 24 hours. The air temperature where the product will be applied is +5 - 30°C.

TECHNICAL SPECIFICATIONS

- **Density:** 1.50 ± 0.02 Mixture
- **Color:** White, Gray and Black
- **Brightness:** Shiny
- **Thinner:** 10% Demarin Epoxy Thinner
- **Consumption:** 6-8 m²/kg
- **Solvent:** Thinner
- **Gun Nozzle Diameter:** 1.2 – 1.4 mm

PACKAGING & STORAGE


- **Packaging:** 1, 4 and 20 kg metal cans
- **Storage Temperature:** +5 - 30 °C
- **Shelf Life:** If stored in original, unopened and undamaged packaging, the primer is suitable for 24 months and the hardener is suitable for 12 months from the date of production.
- **Storage Conditions:** Store in a dry and cool environment with the packaging lids tightly closed.




Attention

The applied surface must be protected from water, moisture and mechanical impacts for at least 24 hours during and after application.





Customizable with color chart



Pedestrian traffic

Material	Concrete	Marble	Wood	Tile	Metal
Waiting Time Between Floors	2 hours	2 hours	2 hours	2 hours	2 hours
Dry to the Touch	4 hours	4 hours	4 hours	4 hours	4 hours
Recommended Application	Roller, Brush	Roller, Brush	Roller, Brush, Airless	Roller, Brush	Roller, Airless
Complete Drying	24 hours	24 hours	24 hours	24 hours	24 hours