



OSMANLI FILLER

It is a single component, solvent based synthetic inspection filler.

USAGE AREAS

-Used on Fiber, Wood, Sheet Metal and Aluminum surfaces and on newly built boats.

APPLICATION INFORMATION

Surface preparation: First of all, the surface to be applied is cleaned of dust, dirt and oil. If there are repair parts, they are repaired in advance and the surfaces are sanded. **Application method:** Do not dilute the **Ottoman Filler**. The product is replaced homogeneously with a trowel or spatula in a 2-minute box. This product can be applied with options such as trowel, spatula etc. The time to reach mechanical resistance is 24 hours. The air temperature where the product will be applied is +5 - 30°C.

TECHNICAL SPECIFICATIONS

- **Density:** 1.40 ± 0.02 Mixture
- **Color:** Off White
- **Brightness:** Matt
- **Thinner:** Not Thinned
- **Consumption:** 1-2 m²/kg


PACKAGING & STORAGE


- **Packaging:** 1, 4 and 25 kg metal cans
- **Storage Temperature:** +5 - 30 °C
- **Shelf Life:** Suitable for use for 12 months from the date of production if stored in original, unopened and undamaged packaging.
- **Storage Conditions:** Store in a dry and cool environment with the packaging lids tightly closed.



Attention

The applied surface must be protected from water, moisture and mechanical impacts for at least 24 hours during and after application.



					
Material	Concrete	Marble	Wood	Tile	Metal
Dry to the Touch	4 hours	4 hours	4 hours	4 hours	x
Recommended Application	Trowel, spatula	Trowel, spatula	Trowel, spatula	Trowel, spatula	x
Complete Drying	24 hours	24 hours	24 hours	24 hours	x