



GLZ-500 WATERPROOF

It is a new generation white moisture and humidity paint with excellent adhesion to all surfaces. It is ready to use, UV resistant, bright and elastic. It is not affected by external weather conditions. It does not yellow, fade or lift over time.

USAGE AREAS

-All kinds of concrete, ceramic, plaster, painted-unpainted surfaces, marble, glass, plastic, metal, tile stone wall, wood etc. are used as moisture and humidity material.

APPLICATION INFORMATION

Surface preparation: First, the surface to be applied is cleaned of dust, dirt and oil. If there are areas that need repair, they are repaired in advance and the surface is sanded. **Application method:** GLZ-500 Waterproof is ready to use, do not dilute. The product is mixed homogeneously in the box for 2 minutes with the help of a mixer. This product can be applied to the surface with a roller or brush. The time to reach mechanical resistance is 24 hours. The air temperature where the product will be applied is +5 - 30°C.

TECHNICAL SPECIFICATIONS

- **Density:** 1.12 ± 0.02 Mixture
- **Color:** White
- **Gloss:** Shiny, matte as desired
- **Thinner:** Not thinned
- **Consumption:** 10-12 m²/kg
- **Solvent:** Thinner

PACKAGING & STORAGE

Packaging: 1, 4 and 15 kg metal cans

Storage Temperature: +5 - 30 °C

Shelf Life: If stored in original, unopened and undamaged packaging, the primer is suitable for 24 months and the hardener is suitable for 12 months from the date of production.

Storage Conditions: Store in a dry and cool environment, with the packaging lids tightly closed.



Attention

The applied surface must be protected from water, moisture and mechanical impacts for at least 24 hours during and after application.



Customizable with color chart



Pedestrian traffic



Ultraviolet resistance



Concrete



Marble



Wood



Tile



Metal

Waiting Time Between Floors

2 hours

2 hours

2 hours

2 hours

2 hours

Dry to the Touch

4 hours

4 hours

4 hours

4 hours

4 hours

Recommended Application

Roller, Brush

Roller, Brush

Roller, Brush

Roller, Brush

Roller

Complete Drying

24 hours

24 hours

24 hours

24 hours

24 hours