



DEMARIN LIQUID MARBLE

(Solvent free)

It is a solvent-free, two-component, marble-looking casting type paint with excellent adhesion to all surfaces.

USAGE AREAS

-Can be applied to all kinds of horizontal surfaces such as wood, parquet, laminate, ceramic, porcelain, tile, marble, metal, stone, wall, etc.

APPLICATION INFORMATION

Surface preparation: First, the surface to be applied should be cleaned of dust, dirt, and oil. Any areas requiring repair should be repaired beforehand, the surface should be sanded, and the surface should be primed with Demarin single-component protective primer if necessary. **Application method:** Demarin liquid marble is ready to use; do not dilute. Mix the product thoroughly with its hardener in a 4:1 ratio (4 parts liquid marble to 1 part hardener) using a mixer for 5 minutes. For metallic and glittery liquid marble colors (pearl, amber, etc.), the mixing ratio is 2:1. This product can be applied to the surface with a roller or squeegee. Once the liquid marble has been mixed with the hardener, it should be used within 40 minutes. It takes 24 hours to reach mechanical strength. The temperature for application should be between +5°C and 30°C. If you have applied white and its shades, Demarin **Utragloss Liquid Glass** should be applied after 1 week to 7 days. Failure to do so may cause color changes.

TECHNICAL SPECIFICATIONS

- **Density:** 1.12 ± 0.02 Mixture
- **Color:** All special colors can be made
- **Brightness:** Shiny, matte as preferred
- **Thinner:** Not thinned
- **Consumption:** 3-4 m²/kg (1 m²/kg if thick casting)
- **Solvent:** -


PACKAGING & STORAGE

- **Packaging:** 1, 4 and 20 kg metal cans
- **Storage Temperature:** +5 - 30 °C
- **Shelf Life:** If stored in original, unopened and undamaged packaging, the primer is suitable for 24 months and the hardener is suitable for 12 months from the date of production.
- **Storage Conditions:** Store in a dry and cool environment with the packaging lids tightly closed.



Attention

The applied surface must be protected from water, moisture and mechanical impacts for at least 24 hours during and after application.



Customizable
with color chart



Pedestrian traffic



Concrete



Marble



Wood



Tile



Metal

Material

Dry to the Touch

5 hours

5 hours

5 hours

5 hours

5 hours

Recommended Application

Roller,
squeegee

Roller,
squeegee

Roller,
squeegee

Roller,
squeegee

Roller,
squeegee

Complete Drying

24 hours

24 hours

24 hours

24 hours

24 hours