

EPOFILLER EPOXY FILLER



It is a two-component, modified epoxy resin and hardener, surface-tolerant, epoxy-based filler used for filling purposes in cold and humid weather.

USAGE AREAS

-Used on Fiber, Wood, Sheet Metal and Aluminum surfaces and on newly built boats.



APPLICATION INFORMATION

Surface preparation: First, the surface to be applied is cleaned of dust, dirt and oil. If there are areas that need repair, they are repaired in advance and the surface is sanded. **Application method:** Do not dilute the **Epofiller Epoxy Filler**. The product is mixed homogeneously with its hardener in a box for 2 minutes at a ratio of 1/1 (1 Paste / 1 hardener) with the help of a trowel or spatula. This product can be applied to the surface with tools such as a trowel, spatula etc. The paste mixed with the hardener should be used within 40 minutes. The time to reach mechanical resistance is 24 hours. The air temperature where the product will be applied is +5 - 30°C.

TECHNICAL SPECIFICATIONS

- **Density:** 1.50 ± 0.02 Mixture
- **Color:** Component A = Mustard yellow, Component B = White
- **Gloss:** Matt
- **Thinner:** Not thinned
- **Consumption:** 2-3 m²/kg

PACKAGING & STORAGE

- **Packaging:** 1, 3 and 20 kg PP buckets
- **Storage Temperature:** +5 - 30 °C
- **Shelf Life:** Suitable for use for 24 months from the date of production if stored in original, unopened and undamaged packaging.
- **Storage Conditions:** Store in a dry and cool environment with the packaging lids tightly closed.



Attention

The applied surface must be protected from water, moisture and mechanical impacts for at least 24 hours during and after application.



Material	Concrete	Marble	Wood	Tile	Metal
Dry to the Touch	4 hours	4 hours	4 hours	4 hours	4 hours
Recommended Application	Trowel, spatula	Trowel, spatula	Trowel, spatula	Trowel, spatula	Trowel, spatula
Complete Drying	24 hours	24 hours	24 hours	24 hours	24 hours