



# GLZ-500 NATURAL STONE VARNISH

It is a solvent-based transparent varnish. It has high saturation properties and high alkali resistance. Thanks to the silicone it contains, it prevents rainwater from penetrating the surface on which it is applied.

## USAGE AREAS

- Suitable for mosaic, tile, porcelain, ceramic, marble, granite, natural stone, wood, concrete, screed, galvanized sheet and aluminum surfaces.

## APPLICATION INFORMATION


**Surface preparation:** First, the surface to be applied is cleaned of dust, dirt and oil. If there are areas that need repair, they are repaired in advance and the surface is sanded. **Application method:** GLZ 500 Varnish is ready to use, do not dilute. The product is mixed homogeneously in the box for 1 minute with the help of a mixer. This product can be applied to the surface with a roller, brush or paint gun. The time to reach mechanical resistance is 24 hours. The air temperature where the product will be applied is +5 - 30°C.

## TECHNICAL SPECIFICATIONS

- **Density:** 1.50 ± 0.02 Mixture
- **Color:** Transparent
- **Gloss:** Shiny and Matt
- **Thinner:** Not Thinned
- **Consumption:** 10-12 m<sup>2</sup>/kg
- **Solvent:** Thinner
- **Gun Nozzle Diameter:** 1.2 – 1.4 mm

## PACKAGING & STORAGE

- **Packaging:** 1, 4 and 15 kg metal cans
- **Storage Temperature:** +5 - 30 °C
- **Shelf Life:** If stored in original, unopened and undamaged packaging, the primer is suitable for 24 months and the hardener is suitable for 12 months from the date of production.
- **Storage Conditions:** Store in a dry and cool environment with the packaging lids tightly closed.

**Attention**

The applied surface must be protected from water, moisture and mechanical impacts for at least 24 hours during and after application.



**Customizable with color chart****Pedestrian traffic****Ultraviolet resistance**

Material	Concrete	Marble	Wood	Tile	Metal
Waiting Time Between Floors	2 hours	2 hours	2 hours	2 hours	2 hours
Dry to the Touch	4 hours	4 hours	4 hours	4 hours	4 hours
Recommended Application	Roller, Brush	Roller, Brush	Roller, Brush, Airless	Roller, Brush	Roller, Airless
Complete Drying	48 hours	48 hours	48 hours	48 hours	48 hours