



# BATHTUB PAINT

(Solvent free)

It is a solvent-free bathtub paint with excellent adhesion to all surfaces.

## USAGE AREAS

-Can be applied to all types of surfaces such as wood, parquet, laminate, ceramic, porcelain, tile, marble, metal, stone, wall, etc.



## APPLICATION INFORMATION


**Surface preparation:** First, the surface to be applied is cleaned of dust, dirt and oil. If there are areas that need repair, they are repaired in advance and the surface is sanded very well. **Application method:** Bathtub Paint is ready to use, do not dilute. The product is mixed homogeneously with its hardener in a 4/1 ratio (4 epoxy / 1 hardener) in a box for 5 minutes with the help of a mixer. This product can be applied to the surface with a roller or brush. Epoxy mixed with hardener must be used within 40 minutes. The time to reach mechanical resistance is 24 hours. The air temperature where the product will be applied is +5 - 30°C. Demarin Utragloss Liquid glass application must be done after 1 week and 7 days, otherwise there may be changes in color.

## TECHNICAL SPECIFICATIONS

- **Density:** 1.12 ± 0.02 Mixture
- **Color:** White
- **Brightness:** Shiny, matte as desired
- **Thinner:** Not thinned
- **Consumption:** 3-4 m<sup>2</sup>/kg (1-2 m<sup>2</sup>/kg if thick casting)
- **Solvent:** -

## PACKAGING & STORAGE


- **Packaging:** 1, 4 and 20 kg metal cans
- **Storage Temperature:** +5 - 30 °C
- **Shelf Life:** If stored in original, unopened and undamaged packaging, the primer is suitable for 24 months and the hardener is suitable for 12 months from the date of production.
- **Storage Conditions:** Store in a dry and cool environment with the packaging lids tightly closed.




### Attention

The applied surface must be protected from water, moisture and mechanical impacts for at least 24 hours during and after application.





Customizable with color chart



Pedestrian traffic

Material	Concrete	Marble	Wood	Tile	Metal
Dry to the Touch	4 hours	4 hours	4 hours	4 hours	4 hours
Recommended Application	Roller, Brush, Airless	Roller, Brush, Airless	Roller, Brush, Airless	Roller, Brush, Airless	Roller, Airless
Complete Drying	48 hours	48 hours	48 hours	48 hours	48 hours