



# DEMAFLEX 900 P.U. TOPCOAT

It is a paint that dries on the surface to form a seamless and waterproof layer. It creates a decorative coating. It is solvent-free. It has elastic properties. It can be applied to dry or slightly damp surfaces. It is very resistant to external weather conditions. It prevents moisture and dampness inside the building.

## APPLICATIONS

-It is used on all types of plaster and painted exterior surfaces, on old coatings such as mineral plaster, ready-made plaster, etc., on exterior facades, on wood and similar surfaces, on raw concrete or prefabricated structures. Due to its high elasticity, it is not affected by cracks that may occur on the building surface.

## APPLICATION INFORMATION

**Surface preparation:** First, the surface to be painted must be cleaned of dust, dirt, and oil. If there are any areas requiring repair, they should be repaired beforehand, and the surface should be sanded. **Application method:** Demaflex 900 P.U. Paint is ready to use. The product is mixed homogeneously with its hardener in a 3:1 ratio (3 paint / 1 hardener) for 5 minutes in the can using a mixer. This product can be applied to the surface with a roller, brush, or spray gun. The paint mixed with the hardener should be used within 40 minutes. The time to reach mechanical resistance is 24 hours. The air temperature for product application is +5 - 30°C.

## TECHNICAL SPECIFICATIONS

- **Density:** 1.50 ± 0.02 Mixture
- **Color:** White, Gray
- **Gloss:** Glossy
- **Thinner:** 10% Demarin Polyurethane thinner
- **Coverage:** 6-8 m<sup>2</sup>/kg
- **Solvent:** Thinner
- **Nozzle Diameter:** 1.2 – 1.4 mm


## PACKAGING & STORAGE

- **Packaging:** 20 kg metal cans
- **Storage Temperature:** +5 - 30 °C
- **Shelf Life:** If stored in original, unopened and undamaged packaging, the paint is suitable for use for 24 months and the hardener for 12 months from the date of manufacture.
- **Storage Conditions:** Store in a dry and cool environment with the packaging lids tightly closed.



## Attention

The applied surface must be protected from water, moisture and mechanical impacts for at least 24 hours during and after application.



Renk Kartelası İle  
Özelleştirilebilir



Yaya Trafiği

## Metarial



Concrete



Marble



Wood



Tile



Metal

Waiting Time Between Floors

2 hours

2 hours

2 hours

2 hours

2 hours

Dry to the Touch

4 hours

4 hours

4 hours

4 hours

4 hours

Recommended Application

Roller, Brush,  
Airless

Roller, Brush,  
Airless

Roller, Brush,  
Airless

Roller, Brush,  
Airless

Roller, Brush,  
Airless

Complete Drying

24 hours

24 hours

24 hours

24 hours

24 hours